

Medium Duty Range

+44 (0) 1932 872348

sales@mobile-scissor-tables.co.uk

Technical Features

All Models

- Safe, light, easy to use and highly manoeuvrable
- High quality robust construction
- A range of maximum lift heights from 840mm to 1550mm
- Manual or battery electric operation
- Optional extras from stainless steel lid to bellows skirt
- Quality British design and manufacture
- Single or double lifts available
- Heavy duty arm, bearings and hydraulics
- All wheels are fitted with sealed bearings and polyurethane tyres
- 2 swivel castors fitted with a total stop brake as standard
- All models fitted with an overload valve and slow lowering valve to control lowering speed
- A unique lift up table top allows safe and easy maintenance - can only be lifted when table is in a closed position
- Each table is issued with operating instructions and a test certificate in conformance with EU Standards EN1570 and BS:5323:1980

Battery Electric Models

- Models include 12v traction battery and charger
- Safety cut-off bar fitted to the underside of the platform stops table from lowering in the case of an obstruction
- Remote push button control up / down operation
- Emergency stop switch
- Safe design plug-in charger
- Strong electrical flex
- Electrical contacts / motors conform to EN1570 / EN60529



Technical Specification

Single Scissor Tables

Capacity	C Raised Height (mm)	D Closed Height (mm)	Operation	E x A Platform W x L (mm)	E x D O/A W x L (mm)	F Handle Height (mm)	Wheel Dia (mm)	Approx. Weight (Kg)	Reference	Approx. Lifting Time
300kg	840	335	Manual	500 x 840	500 x 1050	860	125	83	SC-300-SM	18 Pumps
300kg	840	335	Battery Electric	500 x 840	500 x 1050	860	125	130	SC-300-SE	9 Seconds
500kg	900	340	Manual	610 x 1030	610 x 1320	925	125	109	SC-500-SM	40 Pumps
500kg	900	340	Battery Electric	610 x 1030	610 x 1330	925	125	158	SC-500-SE	12 Seconds

Double Scissor Tables

Capacity	C Raised Height (mm)	D Closed Height (mm)	Operation	E x A Platform W x L (mm)	E x D O/A W x L (mm)	F Handle Height (mm)	Wheel Dia (mm)	Approx. Weight (Kg)	Reference	Approx. Lifting Time
125kg	1420	430	Manual	500 x 840	500 x 1090	860	125	100	SC-125-DM	19 Pumps
125kg	1420	430	Battery Electric	500 x 840	500 x 1130	860	150/125	147	SC-125-DE	9 Seconds
300kg	1350	295	Manual	590 x 840	640 x 1190	900	150/125	110	SC-300-DM	25 Pumps
300kg	1350	295	Battery Electric	590 x 840	640 x 1190	900	150/125	147	SC-300-DE	15 Seconds
450kg	1550	295	Manual	610 x 1030	665 x 1350	910	150/125	143	SC-450-DM	71 Pumps
450kg	1550	295	Battery Electric	610 x 1030	665 x 1350	910	150/125	190	SC-450-DE	26 Seconds

Optional Extras

- Second braked wheel
- Stainless steel top cover
- Ball top
- Bellows safety skirt
- Rubber mat
- Steel, zinc plated roller conveyor top - increases closed/raised height by 60mm

