

Static Range

+44 (0) 1932 872348

sales@mobile-scissor-tables.co.uk

Why Choose an Elevation Static Scissor Table?



Precision Cylinders

Single acting with pipe break valve to prevent rapid lowering in the unlikely event of hydraulic hose failure

Upper Limit Switch

For easy adjustment of the lift stroke making it easy to match with a fixed level

Compact Hydraulic Power Pack

To save valuable space

Safety Trip Bar

Underneath the platform to prevent the table lowering in the event of obstruction preventing entrapment and injury

Circular Steel Rollers

More durable compared to plastic / nylon rollers

Box Steel Construction

Of the scissor arms to give superior lateral stability compared to solid steel

Maintenance Safety Stops

To support the platform in the raised position during servicing

Transparent Oil Tank

For easy oil level checking

- High quality and robust construction
- Compliant with EN1570-1
- Service hatch option available
- Low profile options available



- Hand controller with 3m curly cable
- Customised and fully bespoke solutions
- High intensity operation available
- Can be supplied with lifting eye bolts

SINGLE SCISSOR LIFT TABLES - 500kg -3,000kg							
Model	Max. Load	Platform L x W	Stroke	Closed Height	Approx. Lifting Time	Motor	Net Weight
E1000S	500kg	950 x 600mm	600mm	180mm	8 sec	0.8kW	120kg
E1001S	500kg	1,350 x 800mm	820mm	180mm	12 sec	0.8kW	170kg
E1003S	500kg	1,500 x 1,000mm	820mm	180mm	12 sec	0.8kW	200kg
E1006S	1,000kg	950 x 600mm	600mm	180mm	14 sec	0.8kW	145kg
E1007S	1,000kg	1,200 x 800mm	820mm	180mm	18 sec	0.8kW	175kg
E1008S	1,000kg	1,350 x 800mm	820mm	180mm	21 sec	0.8kW	185kg
E1010S	1,000kg	1,500 x 1,000mm	820mm	180mm	21 sec	0.8kW	215kg
E1012S	1,000kg	2,000 x 1,000mm	1,100mm	230mm	18 sec	1.5kW	340kg
E1016S	1,500kg	1,350 x 800mm	820mm	230mm	24 sec	1.5kW	215kg
E1017S	1,500kg	1,350 x 1,000mm	820mm	230mm	24 sec	1.5kW	225kg
E1018S	1,500kg	1,500 x 1,000mm	820mm	230mm	24 sec	1.5kW	230kg
E1022S	2,000kg	1,350 x 1,000mm	820mm	230mm	22 sec	1.5kW	225kg
E1023S	2,000kg	1,500 x 1,000mm	820mm	230mm	22 sec	1.5kW	230kg
E1025S	2,000kg	2,000 x 1,000mm	1,100mm	230mm	34 sec	1.5kW	350kg
E1029S	2,000kg	2,200 x 1,200mm	1,600mm	300mm	33 sec	2.2kW	470kg
E1031S	2,000kg	3,000 x 1,200mm	1,800mm	300mm	36 sec	2.2kW	590kg
E1033S	3,000kg	1,350 x 800mm	820mm	250mm	18 sec	2.2kW	265kg
HIGH LIFT DOUBLE SCISSOR LIFT TABLES - 200kg - 2,000kg							
Model	Max. Load	Platform L x W	Stroke	Closed Height	Approx. Lifting Time	Motor	Net Weight
E2000S	200kg	900 x 600mm	1,100mm	300mm	19 sec	1.5kW	140kg
E2002S	500kg	900 x 600mm	900mm	600mm	19 sec	1.5kW	225kg
E2008S	1,000kg	1,350 x 1,000mm	1,600mm	450mm	26 sec	2.2kW	310kg
E2016S	1,500kg	1,350 x 1,000mm	1,600mm	450mm	46 sec	2.2kW	360kg
E2021S	2,000kg	1,350 x 1,000mm	1,600mm	450mm	46 sec	2.2kW	410kg
LOW PROFILE SCISSOR LIFT TABLES 600kg - 1000kg							
Model	Max. Load	Platform L x W	Stroke	Closed Height	Approx. Lifting Time	Motor	Net Weight
E6003S	600kg	1,610 x 800mm	970mm	80mm	21 sec	1.5kW	210kg
E6004S	1,000kg	1,200 x 800mm	750mm	100mm	21 sec	1.5kW	240kg
E6006S	1,000kg	1,500 x 1,000mm	800mm	80mm	21 sec	1.5kW	310kg
E6007S	1,000kg	1,610 x 800mm	970mm	80mm	21 sec	1.5kW	290kg
U-SHAPED LOW PROFILE SCISSOR LIFT TABLES 600kg - 2000kg							
Model	Max. Load	Platform L x W	Stroke	Closed Height	Approx. Lifting Time	Motor	Net Weight
E7000	600kg	1,500 x 1,100mm	800mm	80mm	21 sec	1.5kW	210kg
E7001	600kg	1,610 x 1,100mm	970mm	80mm	21 sec	1.5kW	210kg
E7002	1,000kg	1,500 x 1,100mm	800mm	80mm	21 sec	1.5kW	270kg
E7004	1,000kg	1,610 x 1,100mm	970mm	80mm	21 sec	1.5kW	270kg
E7005	1,500kg	1,500 x 1,300mm	800mm	100mm	22 sec	1.5kW	310kg
E7007	1,500kg	1,610 x 1,300mm	970mm	100mm	22 sec	1.5kW	310kg
E7008	2,000kg	1,500 x 1,300mm	800mm	100mm	22 sec	1.5kW	310kg
E7010	2,000kg	1,610 x 1,300mm	970mm	100mm	22 sec	1.5kW	310kg