

Heavy Duty Range

+44 (0) 1932 872348

sales@mobile-scissor-tables.co.uk

Technical Features

All Models

- A range of lift heights from 1050mm to 2900mm
- Manual or battery electric operation
- Robust construction and very easy to manoeuvre
- Unique lift up lid to allow safe and easy maintenance in the closed position
- Quality British manufacture and design
- Single, double and triple lifts available
- Heavy duty arm, bearings and hydraulics
- Nylon bushes fitted at all arm end hinge points
- Heavy duty castor wheels one of which is fitted with a total stop brake as standard - prevents table from moving when loading and unloading
- All models fitted with an overload valve and slow lowering valve to control lowering speed
- The base frame is designed to give low closed height and maximum stability
- Each table is issued with operating instructions and a test certificate in conformance with EU Standards EN1570 and BS:5323:1980

Battery Electric Models

- Models include 12v traction battery and charger
- Safety cut-off bar fitted to the underside of the platform stops table from lowering in the case of an obstruction
- Remote push button control up / down operation
- Emergency stop switch
- Safe design plug-in charger
- Strong electrical flex
- Electrical contacts / motors conform to EN1570 / EN60529



Technical Specification

Single Scissor Tables

Capacity	C Raised Height (mm)	D Closed Height (mm)	Operation	E x A Platform W x L (mm)	E x D O/A W x L (mm)	F Handle Height (mm)	Wheel Dia (mm)	Approx. Weight (Kg)	Reference	Approx. Lifting Time
800kg	1050	360	Manual	840 x 1350	870 x 1630	1040	150/200	222	SC-800-SM	80 Pumps
800kg	1050	360	Battery Electric	840 x 1350	870 x 1630	1040	150/200	270	SC-800-SE	30 Seconds
1250kg	1050	360	Manual	840 x 1350	870 x 1630	1040	150/200	230	SC-1250-SM	80 Pumps
1250kg	1050	360	Battery Electric	840 x 1350	870 x 1630	1040	150/200	278	SC-1250-SE	25 Seconds
1000kg	1050	360	Manual	1000 x 2000	1000 x 2350	1040	150/200	350	SC-1000-SM	80 Pumps
1000kg	1050	360	Battery Electric	1000 x 2000	1000 x 2350	1040	150/200	397	SC-1000-SE	25 Seconds

Double Scissor Tables

Capacity	C Raised Height (mm)	D Closed Height (mm)	Operation	E x A Platform W x L (mm)	E x D O/A W x L (mm)	F Handle Height (mm)	Wheel Dia (mm)	Approx. Weight (Kg)	Reference	Approx. Lifting Time
500kg	1900	490	Manual	840 x 1350	870 x 1630	1040	150/200	306	SC-500-DM	80 Pumps
500kg	1900	490	Battery Electric	840 x 1350	870 x 1630	1040	150/200	352	SC-500-DE	30 Seconds
500kg	1900	490	Manual	840 x 1350	870 x 1630	1040	150/200	315	SC-800-DM	160 Pumps
500kg	1900	490	Battery Electric	840 x 1350	870 x 1630	1040	150/200	363	SC-800-DE	54 Seconds

Triple Scissor Tables

Capacity	C Raised Height (mm)	D Closed Height (mm)	Operation	E x A Platform W x L (mm)	E x D O/A W x L (mm)	F Handle Height (mm)	Wheel Dia (mm)	Approx. Weight (Kg)	Reference	Approx. Lifting Time
500kg	2900	655	Manual	840 x 1350	870 x 1630	1040	150/200	375	SC-500-TM	468 Pumps
500kg	2900	655	Battery Electric	840 x 1350	870 x 1630	1040	150/200	420	SC-500-TE	105 Seconds

Optional Extras

- Second braked wheel
- Stainless steel top cover
- Ball top
- Bellows safety skirt
- Rubber mat
- Steel, zinc plated roller conveyor top - increases closed/raised height by 60mm

